

(b) All commercial hybrid PFDs on the deepwater port must be of the same or similar design and must have the same method of operation.

**§ 149.332 What are the requirements for inflatable lifejackets?**

(a) Each inflatable lifejacket must be approved under approval series 160.176.

(b) All inflatable lifejackets on a deepwater port must:

(1) Be used and stowed according to the procedures contained in the manual required for them under 46 CFR 160.176-21;

(2) Be marked with all limitations, if any; and

(3) Be of the same or similar design and have the same method of operation.

**§ 149.333 What are the marking requirements for lifesaving equipment?**

(a) Each lifeboat, rigid liferaft, and survival capsule must be marked on two opposite outboard sides with the name, number, or other inscription identifying the deepwater port on which it is placed, and the number of persons permitted on the craft. Each paddle or oar for these crafts must also be marked with an inscription identifying the deepwater port. The letters and numbers must be at least 100 millimeters (3.94 inches) high on a contrasting background.

(b) Each inflatable liferaft must be marked to meet 46 CFR 160.151-33, and, after each servicing, marked to meet 46 CFR 160.151-57(m).

(c) Each lifejacket and ring life buoy must be conspicuously marked with the name, number, or other inscription identifying the deepwater port on which it is placed. The letters and numbers must be at least 1.5 inches (38 mm) high on a contrasting background. Lifejackets and ring life buoys that accompany mobile crews to unmanned deepwater ports may be marked with the operator's name and field designation.

UNMANNED DEEPWATER PORT  
REQUIREMENTS

**§ 149.334 Who must ensure compliance with the requirements for unmanned deepwater ports?**

The owner or operator of an unmanned deepwater port must ensure that applicable requirements are complied with on that deepwater port.

**§ 149.335 When are people prohibited from being on an unmanned deepwater port?**

No person may be on an unmanned deepwater port unless all requirements of this part are met.

**§ 149.336 What are the requirements for lifejackets?**

(a) Except as under paragraph (b) of this section, each unmanned deepwater port must have at least one lifejacket complying with § 149.316 of this subpart for each person on the deepwater port. The lifejackets need to be available for use on the port only when persons are onboard.

(b) During helicopter visits, personnel who have aircraft type of lifejackets may use them as an alternative to the requirements of paragraph (a) of this section.

**§ 149.337 What are the requirements for ring life buoys?**

(a) Each unmanned deepwater port must have at least one ring life buoy complying with § 149.320 to this subpart.

(b) If there is no space on the deepwater port for the ring life buoys, they must be on a manned vessel located alongside of the deepwater port while the persons are on the port.

**§ 149.338 What are the requirements for immersion suits?**

(a) Each unmanned deepwater port located north of 32 degrees North latitude must comply with the immersion suit requirements applicable to mobile offshore drilling units under 46 CFR 108.580, and immersion suits must be approved under approval series 160.171. Except as under paragraph (b) of this section, the immersion suits need be on the deepwater port only when persons are on board.